




CBS4LEDS-LO-DIF-DD-HVG

Odyssey Diffused 1200mm Emergency Batten, LP, DALI Driver, Zoneworks XT Hive, Low Output



PRODUCT INFORMATION

Part Number	CBS4LEDS-LO-DIF-DD-HVG
MIC	AUB02910070001
Description	Odyssey Diffused 1200mm Emergency Batten, LP, DALI Driver, Zoneworks XT Hive, Low Output
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface Mount
Dimensions L x W x H	1271mm x 120mm x 108mm
Weight	3.3kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver / Ballast	Driver: LCA 50W 350-1050mA
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	220-240V AC; 50Hz
Power Factor	0.95
Power Consumption	23.5W (Lamps ON Max), 20W (Lamps ON Standby), 1.3W (Lamps OFF Standby)
Inrush Current (Max)	TBC
Earth Leakage	0.134mA
Total Lumen Output	2438lm @ 128lm/W
Operating Temperature	1°C to 40°C
IP Rating	IP20
Impact Rating	N/A
AS2293 Classification	C0=D40, C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
1100635	LED Head Assembly
8002695	240V LED Strip
AUM02970060001 CLIFE-CKIT-HVGEXTA-NP	Driver Pack
1330056	240V Driver
8003580	HVG Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.