

## CBS4LEDS-LO-DIF-DD-HV

CLEVERTRONICS LP ODYSSEY QUANTUM LED DIFFUSED BATTEN - LOW POWER OUTPUT (ZONEWORKS XT HIVE)



PRODUCT INFORMATION	
Part Number	CBS4LEDS-LO-DIF-DD-HV
MIC	AUB02810060001
Description	LP Premium Odyssey Quantum LED Diffused Batten with Dali Driver and LED Emergency Pod
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface Mount
Dimensions L x W x H	1271mm x 120mm x 108mm
Weight	3.3kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver / Ballast	Driver: 50W 350-1050mA
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	23.5W (Max charging, Lamp ON), 20W (Standby, Lamp ON), 1.3W (Standby, Lamp OFF)
Inrush Current (Max)	N/A
Earth Leakage	N/A
Total Lumen Output	2438lm @ 128lm /W
Operating Temperature	1°C to 40°C
IP Rating	IP20
Impact Rating	N/A
AS2293 Classification	C0=D40, C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550050	Battery
8002695	LED Strip
1330056	240V Driver
AUM02870160001 CLIFE-CKIT-HV-NP	Emergency Driver
8003191	RF Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

