

CLEVERTRONICS LP ODYSSEY QUANTUM LED DIFFUSED BATTEN & MICROWAVE SENSOR – LOW POWER OUTPUT (DALI)



PRODUCT INFORMATION

Catalogue Number	CBS4LEDS-LO-DIF-MS-HL-DALI
MIC	AUB02211070002
Description	LP Premium Odyssey Quantum LED Diffused Batten with LED Emergency Pod and Hi/Lo Microwave Sensor Control of the Lamps (10%-100%)
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface Mount
Dimensions L x W x H	1271mm x 120mm x 108mm
Operating Mode	Sustained Minimum to maximum light control via the microwave sensor. Low level comfort light when no presence detected ramping to maximum when presence detected
Testing System	Dali Registered
Battery	Lithium Iron Phosphate 3.2V 3200MAH
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver	Driver: 55w, 500-1200mA, 12-50V
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	2438lm @ 125lm /W
Power Consumption	25W (Max charging, Lamp ON), 22W (Standby, Lamp ON), 1W (Standby, Lamp OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B
1330070	LED HL Driver 55w, 500-1200mA, 12-50V
1190118	SENSOR: Microwave Motion IP20 MC049V
AUM02270170002 CLIFE-CKIT-DALI-NP	Lifelight, Control Only, Dali Reg, LP, No Plug (incl DALI Node)
8003060	PCA: New DALI Node #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order