



CBULK-DALI

CLEVERTRONICS CLP BULKLITE
WEATHERPROOF EMERGENCY LUMINAIRE



PRODUCT INFORMATION	
Part Number	CBULK-DALI
MIC	UKS02220080002
Description	CLP Bulklite Weatherproof Emergency Light
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	346mm x 132mm x 86mm
Weight	1.2kg
Operating Mode	Non-Maintained – Can be adjusted to Maintained via Jumper
Testing System	DALI Registered
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	LED module, L80/B20, 100,000hrs @ Ta 30c 6500K, Ra>80
Diffuser	EXIT decals available separately
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.7Watts (Standby), 4.0Watts (Maintained Standby), 5.0Watts (Max)
Total lumen output	395lm (Emergency) 395lm (Maintained)

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



CBULK-DALI

CLEVERTRONICS CLP BULKLITE
WEATHERPROOF EMERGENCY LUMINAIRE

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP65				
IK Rating	IK08				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)				
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>ADF</td><td>180</td></tr></table>	X	0	ADF	180
X	0	ADF	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550231	BATT:LP 3.2V 6400mAh.200mm lead, No Brkt
8050790	LED: HWSUB: CT10754-D2 Petrus LED Strip - 2835 LP/L10
8002964	PCA: CT10142-L9 6C150 CTP DALI HV ZW UK 250mA Batt

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.