

CBULK-HVG

CLEVERTRONICS CLP BULKLITE WEATHERPROOF EMERGENCY LUMINAIRE



PRODUCT INFORMATION		
Part Number	CBULK-HVG	
MIC	UKS02820100001	
Description	CLP Bulklite Weatherproof Emergency Light	
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate	
Mounting	Surface Mount	
Dimensions L x W x H	346mm x 132mm x 86mm	
Weight	1.2kg	
Operating Mode	Non-Maintained – Can be adjusted to Maintained via Jumper	
Testing System	Zoneworks XT HIVE (RF)	
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics	
Charging Method	Intelligent current limited constant voltage	
Lamp(s)	LED module, L80/B20, 100,000hrs @ Ta 30c 6500K, Ra>80	
Diffuser	EXIT decals available separately	
Operating Voltage	220-240V AC; 50Hz	
Power Consumption	0.7Watts (Standby), 4.0Watts (Maintained Standby), 5.0Watts (Max)	
Total lumen output	395lm (Emergency) 395lm (Maintained)	

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.





CBULK-HVG

CLEVERTRONICS CLP BULKLITE WEATHERPROOF EMERGENCY LUMINAIRE

PRODUCT INFORMATION	
Rated Emergency Duration	180 minutes
IP Rating	IP65
IK Rating	IK08
Operating temperature	0°C to 40°C
Protection	 Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault)
Luminaire Classification	X 0 ADF 180
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS		
PART NUMBER	DESCRIPTION	
1550231	BATT:LP 3.2V 6400mAh.200mm lead, No Brkt	
8050790	LED: HWSUB: CT10754-D2 Petrus LED Strip - 2835 LP/L10	
8002964	PCA: CT10142-L9 6C150 CTP DALI HV ZW UK 250mA Batt	

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.

