



CBULK

LP Premium Bulkite Weatherproof Emergency Light, Enabled with Clevertest Plus



PRODUCT INFORMATION

Part Number	CBULK
MIC	AUS02320280002
Description	LP Premium Bulkite Weatherproof Emergency Light, Enabled with Clevertest Plus
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	346mm x 132mm x 86mm
Weight	1.2kg
Operating Mode	Non-Maintained – Can be adjusted to Maintained via Jumper
Diffuser	EXIT decals available separately
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	LED module, L80/B20, 100,000hrs @ Ta 30c 6500K, Ra>80
Operating Voltage	220-240V AC; 50Hz
Supply Current	0.053A
Power Factor	0.395
Power Consumption	4.7Watts (Max), 3.7Watts (Maintained Standby), 0.4Watts (Standby)
Inrush current (Peak/Duration)	19.4A/134µs
Earth Leakage	N/A
IP Rating	IP65
Impact Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D50, C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550231	Battery
8050790	LED Panel
8002963	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.