

CBULK

CLEVERTRONICS CLP BULKLITE WEATHERPROOF EMERGENCY LUMINAIRE



PRODUCT INFORMATION		
Part Number	CBULK	
MIC	UKS02320090001	
Description	CLP Bulklite Weatherproof Emergency Light, Enabled with Clevertest Plus	
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate	
Mounting	Surface Mount	
Dimensions L x W x H	346mm x 132mm x 86mm	
Weight	1.2kg	
Operating Mode	Non-Maintained – Can be adjusted to Maintained via Jumper	
Testing System	Clevertest Plus Enabled (Not activated by default)	
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics	
Charging Method	Intelligent current limited constant voltage	
Lamp(s)	LED module, L80/B20, 100,000hrs @ Ta 30c 6500K, Ra>80	
Diffuser	EXIT decals available separately	
Operating Voltage	220-240V AC; 50Hz	
Power Consumption	0.4Watts (Standby), 3.7Watts (Maintained Standby), 4.7Watts (Max)	
Total lumen output	395lm (Emergency) 395lm (Maintained)	

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.





CBULK

CLEVERTRONICS CLP BULKLITE WEATHERPROOF EMERGENCY LUMINAIRE

PRODUCT INFORMATION	
Rated Emergency Duration	180 minutes
IP Rating	IP65
IK Rating	IK08
Operating temperature	0°C to 40°C
Protection	 Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault)
Luminaire Classification	X 0 AD 180
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS		
PART NUMBER	DESCRIPTION	
1550231	BATT:LP 3.2V 6400mAh.200mm lead, No Brkt	
8050790	LED: HWSUB: CT10754-D2 Petrus LED Strip - 2835 LP/L10	
8002964	PCA: CT10142-L9 6C150 CTP DALI HV ZW UK 250mA Batt	

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.

