






CCFLED-D2-BLK

Cleverfit Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION	
Part Number	CCFLED-D2-BLK
MIC	AUA02211230001
Description	Cleverfit Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms, Single or Double Sided, Black
Construction	ABS Body and Diffuser with Polycarbonate Clear Tamper Proof Cover
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Earth Leakage	N/A (Class II)
Inrush Current (Peak/Duration)	12.5A/82μS
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 4.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D4 C90=E3.2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II double insulated,  noiseless (clean) earth (ground) terminal (not a protective earth and used for EMC purposes only)

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550105	Battery
8002329	Driver
8002710	LED Strip
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order