



CCFLED-DALI

CLEVERTRONICS CLP CLEVERFIT EXIT



PRODUCT INFORMATION

Part Number	CCFLED-DALI			
MIC	UKA02210010002			
Description	CLP Premium Cleverfit Emergency Exit			
Construction	ABS body and Diffuser with Polycarbonate Clear Tamperproof Cover			
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided			
Dimensions L x W x H	355mm x 80mm x 215mm			
Weight	1.7kg			
Operating Mode	Maintained			
Testing System	DALI Registered			
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Diffuser	All directional inserts included in the box			
Lamp(s)	6 x LED, 100,000 hours			
Operating Voltage	220-240V AC; 50Hz			
Power Consumption	3.7 Watts (Standby), 4.9 Watts (Max)			
Power Factor	0.45			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts			
Luminaire Classification	X	1	AFG	180
Conformity	BS EN 60598-2-22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550090	BATT: LP 3.2V 3200mAh 390mm lead, noBRKT.
8002120	LED: PCA: DLED Cleverfit LightStrip, CT10152-D4
8002318	DRIVER: PCA: LJWELED-32 CT10164-L6_CT10622-L2 6C80 HV Only
8003060	PCA: New DALI #CT10629-Ax

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice