






CCFLED-HVG-BLK

Cleverfit Exit, Surface Mount, LP, Zoneworks XT Hive, All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION

| | |
|--------------------------------|--|
| Part Number | CCFLED-HVG-BLK |
| MIC | AUA02910130001 |
| Description | Cleverfit Exit, Surface Mount, LP, Zoneworks XT Hive, All Pictograms, Single Or Double Sided, Black |
| Construction | ABS Body And Diffuser With Polycarbonate Clear Tamper Proof Cover |
| Mounting | Wall, Ceiling Single-Sided & Ceiling Double-Sided |
| Dimensions L x W x H | 355mm x 80mm x 215mm |
| Weight | 1.8kg |
| Operating Mode | Maintained |
| Testing System | Zoneworks XT HIVE (RF) |
| Battery | Lithium Iron Phosphate, 3.2V 1500mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Diffuser | All directional inserts included in the box |
| Lamp(s) | 6 x LED, 100,000 hours |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 2.8 Watts (Standby), 4.1 Watts (Max) |
| Inrush Current (Peak/Duration) | 11.26A/80μS |
| Earth Leakage | N/A |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C ₀ =E2.5 C ₉₀ =E2 |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) |  |
| Appliance Class |  Class II double insulated,  noiseless (clean) earth (ground) terminal (not a protective earth and used for EMC purposes only) |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------|
| 1550190 | Battery |
| 8002328 | LED Driver |
| 8002120 | PCA Led |
| 8003560 | RF Node |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order