



CCFLED-HVG-BLK

CLEVERTRONICS CLP CLEVERFIT EXIT-BLK



PRODUCT INFORMATION

Part Number	CCFLED-HVG-BLK			
MIC	UKA02810260001			
Description	CLP Premium Cleverfit Emergency Exit - Black			
Construction	ABS body and Diffuser with Polycarbonate Clear Tamperproof Cover			
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided			
Dimensions L x W x H	355mm x 80mm x 215mm			
Weight	1.7kg			
Operating Mode	Maintained			
Testing System	Zoneworks XT HIVE			
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Diffuser	All directional inserts included in the box			
Lamp(s)	6 x LED, 100,000 hours			
Operating Voltage	220-240V AC; 50Hz			
Power Consumption	3.9 Watts (Standby), 4.8 Watts (Max)			
Power Factor	0.45			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts			
Luminaire Classification	X	1	AFG	180
Conformity	BS EN 60598-2-22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550091	Battery
8002710	LED
8002337	Driver
8003330	Node-HVG

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice