



**CCFLED-HVG**  
CLEVERTRONICS CLP CLEVERFIT EXIT  
(ZONWORKS HIVE)



PRODUCT INFORMATION	
Part Number	CCFLED-HVG
MIC	UKA02810010001
Description	CLP Premium Cleverfit Emergency Exit
Construction	ABS body and Diffuser with Polycarbonate Clear Tamper proof Cover
Dimensions L x W x H	355mm x 80mm x 215mm
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Weight	1.2kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	6 x Duris E5 LED, 100,000 hours
Diffuser	All directional inserts included in the box
Operating Voltage	220-240V AC; 50Hz
Power Consumption	3.7 Watts (Standby), 4.9 Watts (Max)
Power Factor	0.45

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



**CCFLED-HVG**  
CLEVERTRONICS CLP CLEVERFIT EXIT  
(ZONWORKS HIVE)

**PRODUCT INFORMATION**

Rated Emergency Duration	180 minutes				
Viewing Distance	30m				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li></ul>				
Luminaire Classification	X	1	AGF	180	
Applicable Standards	BS EN 60598-2-22, BS 5266				
Compliance Marking	UK CA   CE				

**REPLACEMENT PARTS**

PART NUMBER	DESCRIPTION
1550090	Battery
8002120	Emergency LED Strip
8002333	Emergency Driver
8003330	Communication Node – Hive

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.