



## CCFLED-TH-D2-R

Cleverfit Exit, Surface Mount, LP, DALI-2, Theatre Version, Running Man, Single Sided



### PRODUCT INFORMATION

Part Number	CCFLED-TH-D2-R
MIC	AUA02260590001
Description	Cleverfit Exit, Surface Mount, LP, DALI-2, Theatre Version, Running Man, Single Sided
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	355mm x 215mm x 80mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Running man (Must specify diffuser combination)
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.8 Watts (Standby) 4.1 Watts (Max)
Inrush Current (Peak/Duration)	11.26A/80µS
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	Class II double insulated,  noiseless (clean) earth (ground) terminal (not a protective earth and used for EMC purposes only)

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002710	LED Strip
8002329	Driver
8003062	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.