



CCFLED-TH-DS-RAOW

Cleverfit Exit, Surface Mount, CLP, Clevertest Plus, Theatre Version,
Running Man Arrow One Way, Double Sided



PRODUCT INFORMATION

Part Number	CCFLED-TH-DS-RAOW				
MIC	UKA02360100001				
Description	Cleverfit Exit, Surface Mount, CLP, Clevertest Plus, Theatre Version, Running Man Arrow One Way, Double Sided				
Construction	ABS Body and Diffuser with Polycarbonate Clear Tamper Proof Cover				
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided				
Dimensions L x W x H	355mm x 80mm x 215mm				
Weight	1.8kg				
Operating Mode	Maintained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type & Manufacturer	Lithium Iron Phosphate, 3.2V 3200mAh, Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	Theatre Mask with Double-sided Running Man, Arrows (Right Arrow One Side Left Arrow the Other Side)				
Lamp(s)	6 x LED, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	3.0 Watts (Standby), 3.9 Watts (Max)				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)				
Luminaire Classification	X	1	AG	180	
Conformity	BS EN 60598-2-22 Note: Dark format Theatre Exit products are not referenced in BS5499-4 and require a deviation and local sign off for compliance				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550090	Battery
8002356	Driver
8002710	LED Strip

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice