






CCFLED-TH-HV-DS-R

Cleverfit Exit, Surface Mount, LP, Zoneworks XT Hive, Theatre Version, Running Man, Double Sided



PRODUCT INFORMATION

Part Number	CCFLED-TH-HV-DS-R
MIC	AUA00000019801
Description	Cleverfit Exit, Surface Mount, LP, Zoneworks XT Hive, Theatre Version, Running Man, Double Sided
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, Ceiling Double-sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man, Double Sided
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.2 Watts (Standby), 3.6 Watts (Max)
Inrush Current (Max)	12.517A/82µs
Earth Leakage	0.342mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II double insulated  Noiseless (Clean) Earth (Ground) Terminal (Not a Protective Earth and used for EMC Purposes Only)

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8003171	Driver
8002710	LED Strip
8003191	HV Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order