



## CCFLED-TH-HVG-RR

Cleverfit Exit, Surface Mount, Zoneworks Hive, Theatre Version,  
Running Man Arrow Right, Single Sided



PRODUCT INFORMATION	
Part Number	CCFLED-TH-HVG-RR
MIC	AUA02960140001
Description	Cleverfit Exit, Surface Mount, LP, Zoneworks Hive, Theatre Version, Running Man Arrow Right, Single Sided
Construction	ABS Body and Diffuser with Polycarbonate Clear Tamper Proof Cover
Mounting	Wall, Ceiling Single-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Zoneworks HIVE (RF) 2.4 GHz
Battery Type & Manufacturer	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask, Running Man with Right Arrow, Single Sided
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	220-240V~50Hz
Supply Current	0.044A
Power Factor	0.368
Power Consumption	2.2W (Standby) 3.6W (Max)
Inrush Current (Peak/Duration)	12.517A/82µs
Earth Leakage	0.342mA
IP Rating	IP20
Operating temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	<input type="checkbox"/> Class II double insulated,  noiseless (clean) earth (ground) terminal (not a protective earth and used for EMC purposes only)

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550105	Battery
8002710	LED Panel
8003171	Emergency Driver
8003560	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order