



CCFLED-TH-HVG-RR

Cleverfit Exit, Surface Mount, CLP, Clevertest Plus, Theatre Version



PRODUCT INFORMATION				
Part Number	CCFLED-TH-HVG-RR			
MIC	UKA02860010001			
Description	Cleverfit Exit, Surface Mount, CLP, Clevertest Plus, Theatre Version			
Construction	ABS Body and Diffuser with Polycarbonate Clear Tamper Proof Cover			
Mounting	Wall, Ceiling Single-Sided			
Dimensions L x W x H	355mm x 80mm x 215mm			
Weight	1.8kg			
Operating Mode	Maintained			
Testing System	Zoneworks XT HIVE(RF)			
Battery Type & Manufacturer	Lithium Iron Phosphate, 3.2V 3200mAh, Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Diffuser	Theatre mask, Running man with Right Arrow, Single Sided			
Lamp(s)	6 x LED, 100,000 hours			
Operating Voltage	220-240V AC; 50Hz			
Power Consumption	3.3 Watts (Standby), 4.2 Watts (Max)			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)			
Luminaire Classification	X	1	AFG	180
Conformity	BS EN 60598-2-22 Note: Dark format Theatre Exit products are not referenced in BS5499-4 and require a deviation and local sign off for compliance			
REPLACEMENT PARTS				
PART NUMBER	DESCRIPTION			
1550090	Battery			
8002329	Driver			
8002120	LED Strip			
8003330	Hive Node			

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice