



CCFLED-TH-RR

Cleverfit Exit, Surface Mount, CLP, Clevertest Plus,
Theatre Version



PRODUCT INFORMATION

| | | | | | |
|-----------------------------|--|----|-----|----|-----|
| Part Number | CCFLED-TH-RR | | | | |
| MIC | UKA02360030001 | | | | |
| Description | Cleverfit Exit, Surface Mount, CLP, Clevertest Plus, Theatre Version | | | | |
| Construction | ABS Body and Diffuser with Polycarbonate Clear Tamper Proof Cover | | | | |
| Mounting | Wall, Ceiling Single-Sided | | | | |
| Dimensions L x W x H | 355mm x 80mm x 215mm | | | | |
| Weight | 1.8kg | | | | |
| Operating Mode | Maintained | | | | |
| Testing System | Clevertest Plus Enabled (Not activated by default) | | | | |
| Battery Type & Manufacturer | Lithium Iron Phosphate, 3.2V 3200mAh, Clevertronics | | | | |
| Charging Method | Intelligent Current Limited Constant Voltage | | | | |
| Diffuser | Theatre mask, Running man with Right Arrow, Single Sided | | | | |
| Lamp(s) | 6 x LED, 100,000 hours | | | | |
| Operating Voltage | 220-240V AC; 50Hz | | | | |
| Power Consumption | 3.0 Watts (Standby), 3.9 Watts (Max) | | | | |
| Viewing Distance | 30m | | | | |
| Rated Emergency Duration | 180 minutes | | | | |
| IP Rating | IP20 | | | | |
| Operating temperature | 0°C to 40°C | | | | |
| Protection | <ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault) | | | | |
| Luminaire Classification | <table border="1"><tr><td>X</td><td>1</td><td>AG</td><td>180</td></tr></table> | X | 1 | AG | 180 |
| X | 1 | AG | 180 | | |
| Conformity | BS EN 60598-2-22 Note: Dark format Theatre Exit products are not referenced in BS5499-4 and require a deviation and local sign off for compliance | | | | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------|
| 1550090 | Battery |
| 8002356 | Driver |
| 8002120 | LED Strip |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order