



CCFLED-TH-RU

Cleverfit Exit, Surface Mount, CLP, Clevertest Plus, Theatre Version



PRODUCT INFORMATION

Part Number	CCFLED-TH-RU				
MIC	UKA02360040001				
Description	Cleverfit Exit, Surface Mount, CLP, Clevertest Plus, Theatre Version				
Construction	ABS Body and Diffuser with Polycarbonate Clear Tamper Proof Cover				
Mounting	Wall, Ceiling Single-Sided				
Dimensions L x W x H	355mm x 80mm x 215mm				
Weight	1.8kg				
Operating Mode	Maintained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type & Manufacturer	Lithium Iron Phosphate, 3.2V 3200mAh, Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	Theatre mask, Running man with Up Arrow, Single Sided				
Lamp(s)	6 x LED, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	3.0 Watts (Standby), 3.9 Watts (Max)				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">Battery overvoltage & overcurrent protectionBattery deep discharge protectionSupply voltage polarity reversal protectionBattery short-circuit protection (charging will resume upon removal of fault)				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AG</td><td>180</td></tr></table>	X	1	AG	180
X	1	AG	180		
Conformity	BS EN 60598-2-22 Note: Dark format Theatre Exit products are not referenced in BS5499-4 and require a deviation and local sign off for compliance				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550090	Battery
8002356	Driver
8002120	LED Strip

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice