



CCFLED-TH-RU

Cleverfit Exit, Surface Mount, CLP, Clevertest Plus, Theatre Version, Running Man Arrow Up, Single Sided



PRODUCT INFORMATION

Part Number	CCFLED-TH-RU				
MIC	UKA02360040002				
Description	Cleverfit Exit, Surface Mount, CLP, Clevertest Plus, Theatre Version, Running Man Arrow Up, Single Sided				
Construction	ABS Body and Diffuser with Polycarbonate Clear Tamper Proof Cover				
Mounting	Wall, Ceiling Single-Sided				
Dimensions L x W x H	355mm x 80mm x 215mm				
Weight	1.8kg				
Operating Mode	Maintained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type & Manufacturer	Lithium Iron Phosphate, 3.2V 3200mAh, Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	Theatre mask, Running man with Up Arrow, Single Sided				
Lamp(s)	6 x LED, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Supply Current	0.044A				
Power Factor	0.368				
Power Consumption	3.0 Watts (Standby), 3.9 Watts (Max)				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Luminaire Classification	X	1	AG	180	
Compliance Marking					
Conformity	BS EN 60598-2-22 Note: Dark format Theatre Exit products are not referenced in BS5499-4 and require a deviation and local sign off for compliance				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553090	Battery
8003805	Emergency Driver
8002710	LED Panel

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice