



CCFLED

Cleverfit Exit, Surface Mount, CLP, Clevertest Plus, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	CCFLED			
MIC	UKA02310010002			
Description	Cleverfit Exit, Surface Mount, CLP, Clevertest Plus, All Pictograms, Single or Double Sided			
Construction	ABS Body and Diffuser with Polycarbonate Clear Tamper Proof Cover			
Mounting	Wall, ceiling single-sided & ceiling double-sided			
Dimensions L x W x H	355mm x 80mm x 215mm			
Weight	1.8kg			
Operating Mode	Maintained			
Testing System	Clevertest Plus Enabled (Not activated by default)			
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Diffuser	All directional inserts included in the box			
Lamp(s)	6 x Duris E5 LED, 100,000 hours			
Operating Voltage	220-240V AC; 50Hz			
Power Consumption	3.7 Watts (Standby), 4.9 Watts (Max)			
Inrush Current (Max)	13A<82μs			
Earth Leakage	0.35mA			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) 			
Luminaire Classification	X	1	AG	180
Conformity	BS EN 60598.2.22, BS 5266			
Compliance Marking				



CCFLED

Cleverfit Exit, Surface Mount, CLP, Clevertest Plus, All Pictograms,
Single or Double Sided

PRODUCT i	
PART NUMBER	DESCRIPTION
1553090	Battery
8003802	Emergency Driver
8002120	LED Strip

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order