



## CCFPRO-BLK

Cleverfit Pro Exit, Surface Mount, LP, Clevertest Plus, All Pictograms, Single or Double Sided, Black



### PRODUCT INFORMATION

Part Number	CCFPRO-BLK
MIC	UKA02310260001
Description	Cleverfit Pro Exit, Surface Mount, LP, Clevertest Plus, All Pictograms, Single or Double Sided, Black
Construction	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x Duris E3 LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.9 Watts (Max)
Inrush Current (Max)	12.8511A@82 µs
Earth Leakage	0.293mA
Viewing Distance	30m
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li></ul>
Luminaire Classification	X   1   AG   180
Conformity	BS EN 60598-2-22, BS 5266

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	Battery
8002710	LED Strip
8003150	Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order