



CCFPRO-D2-BLK

Cleverfit Pro Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION

Part Number	CCFPRO-D2-BLK
MIC	AUA00000010501
Description	Cleverfit Pro Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms, Single or Double Sided, Black
Construction	Fire-retardant PC/ABS Body with Polycarbonate Diffuser
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.9 Watts (Max)
Inrush Current (Peak/Duration)	15.5A \ 150µs
Earth Leakage	0.321mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D3.2 C90=B16
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8003152	EM Driver
8002710	LED Strip
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order