



CCFPRO-DALI

CLEVERTRONICS CLP CLEVERFIT PRO EXIT (DALI)



PRODUCT INFORMATION					
Part Number	CCFPRO-DALI				
MIC	UKA02210040002				
Description	CLP Premium Cleverfit PRO Emergency Exit				
Construction	PC/ABS body with PC Diffuser				
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided				
Dimensions L x W x H	367mm x 72mm x 214mm				
Weight	2.5kg				
Operating Mode	Maintained				
Testing System	DALI Registered				
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All directional inserts included in the box				
Lamp(s)	6 x Duris E3 LED, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	3.7 Watts (Standby), 4.8 Watts (Max)				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) • Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts 				
Luminaire Classification	<table border="1"> <tr> <td>X</td> <td>1</td> <td>AGF</td> <td>180</td> </tr> </table>	X	1	AGF	180
X	1	AGF	180		
Conformity	BS EN 60598.2.22, BS 5266				

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



CCFPRO-DALI

CLEVERTRONICS CLP CLEVERFIT PRO EXIT
(DALI)

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D1
8003164	PCA: CT10622-L2 6C70 DALI-REG ZW HV ONLY
8003060	PCA: DALI Node #CT10629-Ax

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice