



CCFPRO-HVG

Cleverfit Pro Exit, Surface Mount, CLP, Zoneworks XT Hive, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	CCFPRO-HVG
MIC	UKA02810070001
Description	Cleverfit Pro Exit, Surface Mount, CLP, Zoneworks XT Hive, All Pictograms, Single or Double Sided
Construction	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x Duris E3 LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	3.7 Watts (Standby), 4.8 Watts (Max)
Rated Supply Current	36mA (Standby), 46mA (Max)
Rated Lamp/Module Wattage	1.4 Watts
Power Consumption	3.7 Watts (Standby), 4.8 Watts (Max)
Inrush Current (Max)	13.4A, 240us
Earth Leakage	0.339mA

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



CCFPRO-HVG

Cleverfit Pro Exit, Surface Mount, CLP, Zoneworks XT Hive, All Pictograms, Single or Double Sided

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Viewing Distance	30m				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with I parts				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AFG</td><td>180</td></tr></table>	X	1	AFG	180
X	1	AFG	180		
Conformity	BS EN 60598-2-22, BS 5266				
Compliance Marking					

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553030	Battery
8002710	LED Strip
8003856	Emergency Driver
8003330	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice