



## CCFPRO-TH-D2-RL

Cleverfit Pro Exit, Surface Mount, CLP, DALI-2  
Emergency, Theatre Version, Running Man Arrow  
Left, Single Sided



### PRODUCT INFORMATION

Part Number	CCFPRO-TH-D2-RL
MIC	UKA00000005401
Description	Cleverfit Pro Exit, Surface Mount, CLP, DALI-2 Emergency, Theatre Version, Running Man Arrow Left, Single Sided
Construction	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	DALI-2
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask Running Man, Left Arrow (Must specify diffuser combination)
Lamp(s)	6 x Duris E3 LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Supply Current	0.029A
Power Factor	0.56
Power Consumption	2.8 Watts (Standby), 3.9 Watts (Max)
Inrush Current (Max)	12.851/82μs
Earth Leakage	0.352mA
IP Rating	IP20
Operating temperature	0°C to 40°C
Viewing Distance	20m
Rated Emergency Duration	180 minutes
Luminaire Classification	X   1   AFG   180
Compliance Marking	
Conformity	BS EN 60598.2.22, BS 5266

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553030	Battery
8002710	LED Panel
8003854	Emergency Driver
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order