



CCFPRO-TH-D2-RR

Cleverfit Pro Exit, Surface Mount, LP, DALI-2 Emergency, Theatre Version, Running Man Arrow Right, Single Sided



PRODUCT INFORMATION

Part Number	CCFPRO-TH-D2-RR
MIC	AUA00000046701
Description	Cleverfit Pro Exit, Surface Mount, LP, DALI-2 Emergency, Theatre Version, Running Man Arrow Right, Single Sided
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Wall, Ceiling Single-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask Running Man, Right Arrow (Must specify diffuser combination)
Lamp(s)	6 x Duris LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Supply Current	TBC
Power Factor	TBC
Power Consumption	2.8 Watts (Standby), 3.9 Watts (Max)
Inrush Current (Peak/Duration)	TBC
Earth Leakage	TBC
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8003156	Emergency Driver
8002710	LED Panel
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.