



CCFPRO-TH-D2-RU

Cleverfit Pro Exit, Surface Mount, CLP, DALI Emergency, Theatre Version, Running Man Arrow Up, Single Sided



PRODUCT INFORMATION

Part Number	CCFPRO-TH-D2-RU
MIC	UKA00000000501
Description	Cleverfit Pro Exit, Surface Mount, CLP, DALI Emergency, Theatre Version, Running Man Arrow Up, Single Sided
Construction	PC/ABS body with PC Diffuser
Mounting	Wall or Ceiling
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Operating Voltage	220-240V AC; 50Hz
Charging Method	Intelligent Current Limited Constant Voltage
Inrush Current (Max)	12.851>82μs
Earth Leakage	0.352mA
Power Consumption	2.8 Watts (Standby), 3.9 Watts (Max)
Diffuser	Theatre Mask Running Man, Up Arrow (Must specify diffuser combination)
Lamp(s)	6 x Duris E3 LED, 100,000 hours
Viewing Distance	20m
IP Rating	IP20
Operating temperature	0°C to 40°C
Rated Emergency Duration	180 minutes
Luminaire Classification	X 1 AFG 180
Conformity	BS EN 60598.2.22, BS 5266
Compliance Marking	UKCA CE

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553030	Battery
8002710	LED Strip
8003854	Emergency Driver
8003062	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order