



CCFPRO-TH-DALI-RD

Cleverfit Pro Exit, Surface Mount,
LP,DALI Emergency, Theatre Version,
Running Man Arrow Down, Single Sided



PRODUCT INFORMATION

Part Number	CCFPRO-TH-DALI-RD
MIC	UKA02260010002
Description	CLP Premium Cleverfit PRO Theatre Exit
Construction	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask Running Man, DownArrow(Must specify diffuser combination)
Lamp(s)	6 x Duris E3 LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.9 Watts (Max)
Viewing Distance	20m
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts
Luminaire Classification	X 1 AFG 180
Conformity	BS EN 60598.2.22, BS 5266

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	Battery
8002710	LED Strip
8003156	Emergency Driver
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order



CCFPRO-TH-DALI-RD

Cleverfit Pro Exit, Surface Mount,
LP,DALI Emergency, Theatre Version,
Running Man Arrow Down, Single Sided