



CCFPRO-TH-DALI-RU

Cleverfit Pro Exit, Surface Mount,
LP,DALI Emergency, Theatre Version,
Running Man Arrow Up, Single Sided



PRODUCT INFORMATION	
Part Number	CCFPRO-TH-DALI-RU
MIC	UKA02260050002
Description	Cleverfit Pro Exit, Surface Mount, LP, DALI Emergency, Theatre Version, Running Man Arrow Up, Single Sided
Construction	PC/ABS body with PC Diffuser
Mounting	Wall or Ceiling
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask Running Man, DownArrow(Must specify diffuser combination)
Lamp(s)	6 x Duris E3 LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Inrush Current (Max)	12.851>82µs
Earth Leakage	0.352mA
Power Consumption	2.8 Watts (Standby), 3.9 Watts (Max)
Viewing Distance	20m
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)
Luminaire Classification	X 1 AFG 180
Conformity	BS EN 60598.2.22, BS 5266



CCFPRO-TH-DALI-RU

Cleverfit Pro Exit, Surface Mount,
LP,DALI Emergency, Theatre Version,
Running Man Arrow Up, Single Sided

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550030	Battery
8002710	LED Strip
8003156	Emergency Driver
8003060	DALI Node
N/A	Sensor

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order