



CCFPRO-TH-HVG-DS-R

Cleverfit Pro Exit, Surface Mount, LP, Zoneworks HIVE,
Theatre Version, Running Man, Double Sided



PRODUCT INFORMATION

Part Number	CCFPRO-TH-HVG-DS-R
MIC	AUA00000036301
Description	Cleverfit Pro Exit, Surface Mount, LP, Zoneworks HIVE, Theatre Version, Running Man, Double Sided
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Wall, Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Zoneworks HIVE (RF) 2.4GHz
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask, Running Man
Lamp(s)	6 x Duris LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Supply Current	0.048A
Power Factor	0.38
Power Consumption	2.3 Watts (Standby), 3.5 Watts (Max)
Inrush Current	12.851A @ 82µs
Earth Leakage	0.321mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8003092	Emergency Driver
8002710	LED Panel
8003560	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order