CCIRC-MS-HL-HVG



Circlite IP54 Weatherproof Circular Emergency, LP, Sustained, Motion Sensor, Zoneworks XT Hive 2.4GHz



PRODUCT INFORMATION	
Part Number	CCIRC-MS-HL-HVG
MIC	UKC02810020001
Description	Circlite IP54 Weatherproof Circular Emergency, LP, Sustained, Motion Sensor, Zoneworks XT Hive 2.4GHz
Construction	Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	327mm (Diameter) x 100mm (Height)
Weight	1.8kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Diffuser	Polycarbonate Diffuser
Charging Method	Intelligent current limited constant voltage
Lamp(s)	LED module, 4,000K natural white, 50,000h life, Ra>80
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 17 Watts (Max)
Total lumen output	1460lm @ 105lm/W
EM Lumen Output	374lm

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.







Circlite IP54 Weatherproof Circular Emergency, LP, Sustained, Motion Sensor, Zoneworks XT Hive 2.4GHz

PRODUCT INFORMATION						
Rated Emergency Duration	180 minutes					
IP Rating	IP54					
Operating temperature	0°C to 30°C					
Protection	 LED driver – Over temperature protection, Overload protection, Short-circuit protection, No-load protection Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) 					
Luminaire Classification	Х	2	ADF	180		
Applicable Standards	BS EN 60598-2-22, BS 5266					
Compliance Marking	UK CE					

REPLACEMENT PARTS		
PART NUMBER	DESCRIPTION	
1550230	Battery	
8011800	LED	
1330036	240V Driver	
UKM02870200001	EM Driver	
8003330	Replacement Communications Node HIVE	

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.

