




CCIRC
CLEVERTRONICS LP CIRCULAR LED EMERGENCY LUMINAIRE



PRODUCT INFORMATION

Part Number	CCIRC
MIC	AUC02310010001
Description	LP Premium Circular LED Emergency Luminaire, Trim colour white, Enabled with Clevertest Plus
Construction	Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	327mm (Diameter) x 100mm (Height)
Weight	1.8 kg
Operating Mode	Sustained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver	LED Driver - 20w Stallion, 380mA
Lamp(s)	LED module, 4,000K natural white, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.93
Total Lumen Output	1460lm @118lm/W (based on Non-EM version)
Power Consumption	15 Watts (Lamp ON Max Charge), 13W (Lamp ON Standby Charge), 1 Watt (Lamp OFF Standby)
IP Rating	IP54
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
8011800	LED: SUBASSY: HT10585-A2 CCIRC LED 9S8P 2835 4000K
1330091	LED Driver - 20w Stallion, 380mA
AUM02370470001 CLIFE-CKIT-NP-220	Lifelight, Control Only, LP,CTP,OWC,220mA, No Plug

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order