



CCIRC
CLEVERTRONICS CLP CIRCULAR LED EMERGENCY





PRODUCT INFORMATION	
Part Number	CCIRC
MIC	UKC02310010001
Description	CLP Premium Circular LED Emergency Luminaire, Trim colour white
Construction	Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	327mm (Diameter) x 100mm (Height)
Weight	1.8kg
Operating Mode	Sustained
Testing System	Clevertest Plus
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	LED module, 4,000K natural white, 50,000h life, Ra>80
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 16.8 Watts (Max)
Total lumen output	1460lm
EM lumen output	374lm

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



CCIRC
CLEVERTRONICS CLP CIRCULAR LED EMERGENCY

PRODUCT INFORMATION				
Rated Emergency Duration	180 minutes			
IP Rating	IP54			
Operating temperature	0°C to 30°C			
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts			
Luminaire Classification	X	2	AD	180
Applicable Standards	BS EN 60598-2-22, BS 5266			
Compliance Marking	 			

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead. BRKT
8011800	LED : SUBASSY: HT10585-A2 CCIRC LED 9S8P 2835 4000K
1330091	LED Driver - 11W Stallion, 360mA
UKM02370250001	EM Driver: CLIFE-CKIT-220 Lifelight, Control Only, LP, CTP, OWC, 220mA

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.