



CFLLED-BLK

Supalite Twin Spot Emergency, Surface Mount, LP, Clevertest Plus, Black



PRODUCT INFORMATION	
Part Number	CFLLED-BLK
MIC	UKT00000007301
Description	Supalite Twin Spot Emergency, Surface Mount, LP, Clevertest Plus, Black
Material	Polycarbonate
Mounting	Surface Mounted
Dimensions	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm.
Weight	1.3kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED Heads (adjustable), 155lm per Lamp Head (Emergency)
Operating Voltage	220-240V AC; 50Hz
Supply Current	0.054A
Power Factor	0.366
Total Lumen Output	310lm (Emergency)
Power Consumption	0.4W/2.7W (STANDBY/MAX)
Inrush Current (Peak/Duration)	TBC
Earth Leakage	TBC
IP Rating	IP20
Operating Temperature	0°C to 40°C
Rated Emergency Duration	180 Minutes
Compliance Marking	
Luminaire Classification	X 0 AD 180
Conformity	BS EN 60598-2-22, BS 5266



CFLLED-BLK

Supalite Twin Spot Emergency, Surface Mount, LP,
Clevertest Plus, Black

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553230	Battery
8003851	Emergency Driver
1100956	LED Head Assembly, Left
1100957	LED Head Assembly, Right

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order