



CFLLED-D2

Supalite Twin Spot Emergency, Surface Mount, CLP, DALI-2 Emergency



PRODUCT INFORMATION

Part Number	CFLLED-D2				
MIC	UKT00000006101				
Description	Supalite Twin Spot Emergency, Surface Mount, CLP, DALI-2 Emergency				
Construction	Polycarbonate				
Mounting	Surface Mounted				
Dimensions L x W x H	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm				
Weight	1.3kg				
Operating Mode	Non-maintained				
Testing System	DALI-2				
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	2 x LED Heads (adjustable), 160lm per lamp head				
Operating Voltage	240V AC; 50Hz				
Supply Current	0.035A				
Power Factor	0.321				
Total Lumen Output	320lm (Emergency total)				
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)				
Inrush Current (Peak/Duration)	14.0A / 77µs				
Earth Leakage	N/A				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Compliance Marking					
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>ADF</td><td>180</td></tr></table>	X	0	ADF	180
X	0	ADF	180		
Conformity	BS EN 60598.2.22, BS 5266				
Appliance Class	☐ Class II double insulated				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
8003143	Emergency Driver
1100955	LED Flood Lamp Head
1100954	LED Flood Lamp Head
8003062	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice