



CFLLED-DALI-BLK


CLEVERTRONICS CLP LED SUPALITE -BLACK



PRODUCT INFORMATION

Part Number	CFLLED-DALI-BLK
MIC	UKE02210020002
Description	CLP Premium Supalite LED Flood Unit, Surface Mounted Emergency Light, Black
Construction	Polycarbonate
Mounting	Surface Wall Mount & supplied with flex and plug (the flex and plug can be removed to allow for a hard-wired connection)
Dimensions L x W x H	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm.
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery Type & Manufacturer	Lithium Iron Phosphate 3.2V 6400mAh, Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED Heads (adjustable), 155lm per Lamp Head
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Total lumen output	310lm (Emergency)

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	1°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts				
Luminaire Classification	X	0	ADF	180	
Applicable Standards	BS EN 60598-2-22, BS 5266				
Compliance Marking					

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
1100956	LED Flood Lamp Head Ass, Cable & Ctr, Left, Blk
1100957	LED Flood Lamp Head Ass, Cable & Ctr, Right, Blk
8003143	PCA:CFLLED UK CT10142-L9 CTP UK
8003060	PCA: New DALI #CT10629-Ax

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.