

CLEVERTRONICS CLP LED SUPALITE (DALI)



PRODUCT INFORMATION

Catalogue Number	CFLLED-DALI
MIC	UKE02210010002
Description	CLP Premium Supalite LED Flood Unit, Surface Mounted Emergency Light
Construction	Polycarbonate
Mounting	Surface Mounted. Supplied with Flex
Dimensions L x W x H	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm.
Weight	1.3kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED Heads (adjustable), 155lm per Lamp Head (Emergency)
Operating Voltage	220-240V AC; 50Hz
Total lumen output	310lm (Emergency)
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) 			
Luminaire Classification	X	0	ADF	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
1100955	LED Flood Lamp Head Ass, Cable & Cnnctr. Right
1100954	LED Flood Lamp HeadAss,Cable&Cnnctr,Left
8003143	PCA:CFLLED UK CT10142-L9 CTP UK
8003060	PCA: New DALI #CT10629-Ax

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.