



CFLLED-HVG-BLK

CLEVERTRONICS CLP LED SUPALITE (ZONWORKS HIVE)



PRODUCT INFORMATION	
Part Number	CFLLED-HVG-BLK
MIC	UKE02810020001
Description	CLP Premium Supalite LED Flood Unit, Surface Mounted Emergency Light, Black
Construction	Polycarbonate
Dimensions L x W x H	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm.
Mounting	Surface Mounted
Weight	1.3kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED Heads (adjustable), 155lm per Lamp Head (Emergency)
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Total lumen output	310lm (Emergency)

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



CFLLED-HVG-BLK

CLEVERTRONICS CLP LED SUPALITE (ZONWORKS HIVE)

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts				
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>ADF</td><td>180</td></tr></table>	X	0	ADF	180
X	0	ADF	180		
Applicable Standards	BS EN 60598-2-22, BS 5266				
Compliance Marking					

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
1100956	LED Head Assembly - Right
1100957	LED Head Assembly - Left
8003143	Emergency Driver
8003330	Emergency Node - Hive

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.