



CFLLED-HVG

Supalite Twin Spot Emergency, Surface Mount, CLP, Zoneworks Hive



PRODUCT INFORMATION

Part Number	CFLLED-HVG			
MIC	UKE02810010002			
Description	Supalite Twin Spot Emergency, Surface Mount, CLP, Zoneworks Hive			
Construction	Polycarbonate			
Mounting	Surface Mounted.			
Dimensions L x W x H	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm.			
Weight	1.3kg			
Operating Mode	Non-maintained			
Testing System	Zoneworks HIVE (RF) 2.4GHz			
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Lamp(s)	2 x LED Heads (adjustable), 160lm per lamp head			
Operating Voltage	240V AC; 50Hz			
Supply Current	0.054A			
Power Factor	0.366			
Total Lumen Output	320lm (Emergency total)			
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)			
Inrush Current (Max)	14.0A, 77us			
Earth Leakage	N/A			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Compliance Marking				
Luminaire Classification	X	0	ADF	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553230	Battery
8003851	Emergency Driver
1100955	LED Flood Lamp Head
1100954	LED Flood Lamp Head
8003330	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice