

CLEVERTRONICS CLP LED SUPALITE



PRODUCT INFORMATION

Catalogue Number	CFLLED
MIC	UKE02310010001
Description	CLP Premium Supalite LED Flood Unit, Surface Mounted Emergency Light Clevertest Plus Enabled
Construction	Polycarbonate
Mounting	Surface Mounted. Supplied with Flex
Dimensions L x W x H	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm.
Weight	1.3kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED Heads (adjustable), 155lm per Lamp Head (Emergency)
Operating Voltage	220-240V AC; 50Hz
Total lumen output	310lm (Emergency)
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) 			
Luminaire Classification	X	0	AD	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
1100955	LED Flood Lamp Head Ass, Cable & Cnnctr. Right
1100954	LED Flood Lamp HeadAss,Cable&Cnnctr,Left
8003143	PCA:CFLLED UK CT10142-L9 CTP UK

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.