



CGELED-80-WM-HV-R

LP WALL MOUNT GIGANTOR EXIT



PRODUCT INFORMATION

Part Number	CGELED-80-WM-HV-R
MIC	AUA02810120002
Description	LP Premium Wall Mount Gigantor Exit, 80 Metre Viewing Distance
Construction	Powder Coated Metal Frame with Acrylic Diffuser
Mounting	Wall Mount, Single-sided
Dimensions L x W x H	1305mm x 170mm x 560mm
Weight	21kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 1 x 3.2V 6400mAh (EXIT), 1 x 6.4V 3200mAh (EM)
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Running Man (Must Specify Diffuser Combination)
Lamp(s)	Exit: LED Strip Module, 4,000K Natural White, Ra>80, LED Lifetime: >100,000hrs (AS/NZS2293.3 LSL=39Y/00M), Ta 40°C EM: 2 x 3W LED (Lifetime Warranty on the Lamp head and Loom Assembly)
Operating Voltage	220-240V AC; 50Hz
Power Consumption	23.6W (Standby), 30.6W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Viewing Distance	80m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550290	Battery - Exit
1550230	Battery - Emergency
1100869	Lifelight Pro Head Assembly
8002690	Emergency LED Panel
1330054	240V Driver LED Head Assembly
AUM02870530001 CCPLED-38V120C-CKIT-HV	Emergency Driver - Exit
AUM02870110001 CLIFE-PRO-CKIT-HV-NP	Emergency Driver
8003182	Node - HIVE

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order