

CIRC

Circlite, Non-emergency, Switchable Colour & Output, White



D (N)	oino	
Part Number	CIRC	
MIC	AUC04610050001	
Description	Circlite, Non-emergency, Switchable Colour & Output, White	
Colour CCT	Switchable 3000K / 4000K (Default) / 5700K	
Switchable output	High (Default) / Low	
Material	Base & Diffuser: Polycarbonate	
Mounting	Ceiling/Wall Surface Mount	
Sensor Capability	N/A	
Dimensions	⊘350mm x 81mm	
Weight	1.22kg	
Operating Mode	N/A	
Testing System	N/A	
Battery	N/A	
Charging Method	N/A	
Driver	30W Stallion, SP2, Dip Switch, 250/500mA	
Lamp(s)	LED Panel, 3,000K warm white, 4,000K natural white, 5,700K cool white, Ra>80 L70/B50 Ta 40°C; LM80 Report >54,000hr, Projected 166,000hr L70/B50 Ta 25°C; LM80 Report >54,000hr, Projected 166,000hr L80/B20 Ta 40°C; LM80 Report >54,000hr, Projected 94,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr	
Operating Voltage	220-240V~ 50Hz	
Total Lumen Output	2257 lm (112.8 lm/W) @default (refer to next page for details)	
Power Consumption	20.6W (refer to next page for details)	
Supply Current	0.09A +/-20mA	
Inrush Current (Max)	7.10 A < 28 μs	
Earth Leakage	0.125mA	
IP Rating	IP20	
IK Rating	IK03	
LED MacAdam	5	
Operating Temperature	1°C to 40°C	
AS2293 Classification	NA	
Applicable Standards	AS/NZS3820, AS/NZS60598, CISPR15	
Compliance Marking		





CIRC

Circlite, Non-emergency, Switchable Colour & Output, White

REPLACEMENT PARTS		
PART NUMBER	DESCRIPTION	
N/A	Battery	
1330102	240V Driver	
8051425	LED Panel	
N/A	Emergency Driver	
N/A	Sensor	

Power Consumption &	Output (500mA)		
Lumen Output	Lamp On	Lumen Output	
3000K	20.6W	2141 lm	
4000K	20.0W	2257 lm	
5700K	20.6W	2192 lm	

Power Consumption &	Output (250mA)		
Lumen Output	Lamp On	Lumen Output	
3000K	10.4W	1121 lm	
4000K	10.2W	1159 lm	
5700K	10.4W	1148 lm	

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

