



CIRC

Circlite, Non-emergency, Switchable Colour & Output,
White



PRODUCT INFORMATION	
Part Number	CIRC
MIC	UKC04610060001
Description	Circlite, Non-emergency, Switchable Colour & Output, White
Colour CCT	Switchable 3000K / 4000K (Default) / 5700K
Switchable output	High (Default) / Low
Material	Base & Diffuser: Polycarbonate
Mounting	Ceiling/Wall Surface Mount
Sensor Capability	N/A
Dimensions	Ø350mm x 81mm
Weight	1.22kg
Operating Mode	N/A
Testing System	N/A
Battery	N/A
Charging Method	N/A
Driver	30W Stallion, SP2, Dip Switch, 250/500mA
Lamp(s)	LED Panel, 3,000K warm white, 4,000K natural white, 5,700K cool white, Ra>80 L70/B50 Ta 40°C; LM80 Report >54,000hr, Projected 166,000hr L70/B50 Ta 25°C; LM80 Report >54,000hr, Projected 166,000hr L80/B20 Ta 40°C; LM80 Report >54,000hr, Projected 94,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr
Operating Voltage	220-240V~ 50Hz
Total Lumen Output	2257 lm (112.8 lm/W) @default (refer to next page for details)
Power Consumption	20.6W (refer to next page for details)
Supply Current	0.09A +/-20mA
Inrush Current (Max)	7.10 A < 28 µs
IP Rating	IP20
IK Rating	IK03
LED MacAdam	5
Operating Temperature	0°C to 40°C
Rated Emergency Duration	N/A
Applicable Standards	BS IEC 60598-1, BS EN IEC 55015, BS EN 61547, BS EN IEC 61000-3-2
Compliance Marking	
Luminaire Classification	N / A



CIRC

Circlite, Non-emergency, Switchable Colour & Output,
White

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
N/A	Battery
1330102	240V Driver
8051425	LED Panel
N/A	Emergency Driver
N/A	Sensor

Power Consumption & Lumen Output	Output (500mA)	
	Lamp On	Lumen Output
3000K	20.6W	2141 lm
4000K	20.0W	2257 lm
5700K	20.6W	2192 lm

Power Consumption & Lumen Output	Output (250mA)	
	Lamp On	Lumen Output
3000K	10.4W	1121 lm
4000K	10.2W	1159 lm
5700K	10.4W	1148 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order