



CJELED-40-D2-BLK

Jumbo 40m Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION

| | |
|--------------------------------|--|
| Part Number | CJELED-40-D2-BLK |
| MIC | AUA00000040401 |
| Description | Jumbo 40m Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms, Single or Double Sided, Black |
| Construction | Powder Coated Metal Frame with Acrylic Diffuser |
| Mounting | Universal Mount |
| Dimensions L x W x H | 630mm x 100mm x 320mm |
| Weight | 7.3kg |
| Operating Mode | Maintained |
| Testing System | DALI-2 |
| Battery | Lithium Iron Phosphate, 3.2V 3200mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Diffuser | All pictograph directional inserts included in the box (One box solution) |
| Lamp(s) | 12 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar – 100,000hrs |
| Operating Voltage | 240V AC; 50Hz |
| Supply Current | 0.056A |
| Power Factor | 0.40 |
| Power Consumption | 3.2 Watts (Standby), 5.6 Watts (Max) |
| Inrush Current (Peak/Duration) | 11.625A |
| Earth Leakage | 0.371mA |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C ₀ =D6.3 C ₉₀ =E3.2 |
| Viewing Distance | 40m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|----------------|------------------|
| 3730040 | Battery |
| 8002470 | LED Panel |
| AUM02270670001 | Emergency Driver |
| 8003062 | Node |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.