



CJELED-40-HV-BLK

CLEVERTRONICS LP JUMBO UNIVERSAL MOUNT LED EXIT - BLACK



PRODUCT INFORMATION

Part Number	CJELED-40-HV-BLK
MIC	AUA02810360001
Description	LP Premium Jumbo Emergency Exit, Black
Construction	Powder Coated Metal Frame with Acrylic Diffuser
Mounting	Universal Mount
Dimensions L x W x H	630mm x 100mm x 320mm
Weight	7.3kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box (One box solution)
Lamp(s)	12 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar – 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	3.2 Watts (Standby), 5.6 Watts (Max, during first 16hr charge)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D6.3 C ₉₀ =E3.2
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550092	BATT:LP 3.2V 3200mAh 260mm lead, NB, Sleeve
8002470	PCA:Duris E5 Strip for LJELED. CT10050-D2
AUM02870130001 CJELED-40-CKIT-HV-110	Jumbo LED Exit, Control Kit, LP, HV (incl. Hive node)
8003191	PCA: RF Node CT10678-A12 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.