



## CJELED-40

### CLEVERTRONICS LP JUMBO UNIVERSAL MOUNT LED EXIT



#### PRODUCT INFORMATION

Part Number	CJELED-40
MIC	AUA02310120002
Description	LP Premium Jumbo Emergency Exit, Enabled with Clevertest Plus
Construction	Powder Coated Metal Frame with Acrylic Diffuser
Mounting	Universal Mount
Dimensions L x W x H	630mm x 100mm x 320mm
Weight	7.3kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box (One box solution)
Lamp(s)	12 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar – 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	3.2 Watts (Standby), 5.6 Watts (Max, during first 16hr charge)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D6.3 C <sub>90</sub> =E3.2
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

#### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
3730040	BATTERY: Sub-Assy, Batt 1550092 LP 3.2V 3.2Ah in Enclosure
8002470	LED: PCA:Duris E5 Strip for LJELED. CT10050-D2
AUM02370110001 CJELED-40-CKIT-110	DRIVER PACK: Jumbo LED Exit, Control Kit, LP, OWC

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.