

CJELED-50-HVG

CLEVERTRONICS CLP JUMBO LED EXIT UNIVERSAL MOUNT (ZONEWORKS HIVE)



Part Number	C IEI ED 50 HVC					
	CJELED-50-HVG					
MIC	UKA02810020001					
Description	CLP Premium Jumbo Emergency Exit, 50 metre viewing Distance					
Construction	Powder coated Metal Frame with Acrylic Diffuser					
Mounting	Surface Mount					
Dimensions L x W x H	630mm x 320mm x 100mm					
Weight	7.3kg					
Operating Mode	Maintained					
Testing System	Zoneworks XT HIVE (RF)					
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics					
Charging Method	Intelligent Current Limited Constant Voltage					
Diffuser	All directional inserts included in the box					
Lamp(s)	12 x High Intensity LED, surface mounted onto a replaceable lamp bar – 100,000hrs					
Operating Voltage	220-240V AC; 50Hz					
Total Lumen Output	56lm (Downward Emergency Output)					
Power Consumption	3.2 Watts (Standby), 5.6 Watts (Max)					
Viewing Distance	50m					
Rated Emergency Duration	180 minutes					
IP Rating	IP20					
Operating temperature	0°C to 40°C					
Protection	Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts					
Luminaire Classification	Х	1	AFG	180		
Conformity	BS EN 60598-2-22, BS 5266					

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice





CJELED-50-HVG

CLEVERTRONICS CLP JUMBO LED EXIT UNIVERSAL MOUNT (ZONEWORKS HIVE)

REPLACEMENT PARTS			
PART NUMBER	DESCRIPTION		
1550229	BATT:LP 3.2V 6400mAh 200mm lead, Sleeve		
8002470	PCA:Duris E5 Strip for LJELED.CT10050-D1		
UKM02870080001	CJELED-50-CKIT-HVG-110, Jumbo LED Exit, Control Kit, HVG, LP, 110mA		
8003250	PCA: UK RF Node CT10720-A1 Ext Antenna		

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

