

## CJELED-50

## CLEVERTRONICS CLP JUMBO LED EXIT UNIVERSAL MOUNT



Part Number	CJELED-50
MIC	UKA02310060001
Description	CLP Premium Jumbo Emergency Exit, 50 metre viewing Distance, Enabled with Clevertest Plus
Construction	Powder coated Metal Frame with Acrylic Diffuser
Mounting	Surface Mount
Dimensions L x W x H	630mm x 320mm x 100mm
Weight	7.3kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x High intensity LED, surface mounted onto a replaceable lamp bar – 100,000hrs
Operating Voltage	220-240V AC; 50Hz
Total Lumen Output	56lm (Downward Emergency Output)
Power Consumption	3.2 Watts (Standby), 5.6 Watts (Max)
Viewing Distance	50m
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Protection	<ul> <li>Battery overvoltage &amp; overcurrent protection</li> <li>Battery deep discharge protection</li> <li>Supply voltage polarity reversal protection</li> <li>Battery short-circuit protection (charging will resume upon removal of fau</li> <li>Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts</li> </ul>
Luminaire Classification	X 1 AG 180
Conformity	BS EN 60598-2-22, BS 5266

<sup>\*</sup>Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice





## CJELED-50 CLEVERTRONICS CLP JUMBO LED EXIT UNIVERSAL MOUNT

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550229	BATT:LP 3.2V 6400mAh 200mm lead, Sleeve
8002470	PCA:Duris E5 Strip for LJELED.CT10050-D1
UKM02370140001	CJELED-50-CKIT-110, Jumbo LED Exit, Control Kit, LP, 110mA

<sup>\*</sup>Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

