



CJWELED-40-D2

Jumbo 40m Weatherproof Exit, Surface Mount, LP, DALI-2, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	CJWELED-40-D2
MIC	AUA02220290001
Description	Jumbo 40m Weatherproof Exit, Surface Mount, LP, DALI-2, All Pictograms, Single or Double Sided
Construction	Polycarbonate
Mounting	Wall mount, Single-sided Ceiling mount, Single & Double-sided
Dimensions L x W x H	570mm x 117mm x 340mm
Weight	5.6kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included
Lamp(s)	12 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	3.2 Watts (Standby), 5.1 Watts (Max)
Inrush Current (Max)	11.625A
Earth Leakage	0.371mA
IP Rating	IP66
IK Rating	IK09
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D6.3 C ₉₀ =E4
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
8050640	LED Strip
AUM02270670001	EM Driver
CJELED-40-CKIT-D2-110	
8003062	D2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.